



# Balance Clips



Variation in manufacturing can require the use of "balance clips" to insure smooth operating performance of fans and blowers. Universal's standard and custom balance clips solve this problem in a whirl!

Part Number	Standard Pack	Net Unit Weight			
		Pounds	Ounces	Grams	Grains
6048	50,000	0.00060	0.00960	0.272	4.200
6374	1,000	0.00070	0.01120	0.318	4.900
7186	25,000	0.00070	0.01120	0.318	4.900
4995	4,500	0.00090	0.01440	0.408	6.300
6378	1,000	0.00090	0.01440	0.408	6.300
6514	40,000	0.00100	0.01600	0.454	7.000
7200	40,000	0.00100	0.01600	0.454	7.000
7227	25,000	0.00100	0.01600	0.454	7.000
6047	40,000	0.00130	0.02080	0.590	9.100
6515	25,000	0.00157	0.02512	0.712	10.990
7179	10,000	0.00160	0.02560	0.726	11.200
7586	12,000	0.00160	0.02560	0.726	11.200
6375	22,000	0.00170	0.02720	0.771	11.900
7228	20,000	0.00170	0.02720	0.771	11.900
4996	35,000	0.00180	0.02880	0.816	12.600
6132	25,000	0.00180	0.02880	0.816	12.600
6049	1,000	0.00220	0.03520	0.998	15.400
7201	10,000	0.00230	0.03680	1.043	16.100
6376	12,000	0.00250	0.04000	1.134	17.500
7400	11,000	0.00280	0.04480	1.270	19.600
7599	11,000	0.00280	0.04480	1.270	19.600
7183	7,000	0.00290	0.04640	1.315	20.300
7202	1,000	0.00300	0.04800	1.361	21.000
4997	8,000	0.00370	0.05920	1.678	25.900
6133	14,000	0.00370	0.05920	1.678	25.900
6470	1,000	0.00380	0.06080	1.724	26.600
4765	12,000	0.00400	0.06400	1.814	28.000
7180	7,000	0.00400	0.06400	1.814	28.000
7203	1,000	0.00490	0.07840	2.223	34.300
4998	5,000	0.00510	0.08160	2.313	35.700

REV7.1-07



# Balance Clips



Variation in manufacturing can require the use of "balance clips" to insure smooth operating performance of fans and blowers. It's time to take the Universal Metal Products balance clips for a spin!

Part Number	Standard Pack	Net Unit Weight			
		Pounds	Ounces	Grams	Grains
6136	8,000	0.00550	0.08800	2.495	38.500
4982	9,000	0.00560	0.08960	2.540	39.200
6493	1,000	0.00560	0.08960	2.540	39.200
7204	1,000	0.00610	0.09760	2.767	42.700
6054	1,000	0.00620	0.09920	2.812	43.400
4999	3,500	0.00680	0.10880	3.084	47.600
6377	1,000	0.00680	0.10880	3.084	47.600
6134	6,000	0.00740	0.11840	3.357	51.800
4849	5,000	0.01030	0.16480	4.672	72.100
6000	2,500	0.01040	0.16640	4.717	72.800
6135	4,500	0.01040	0.16640	4.717	72.800
6001	1,500	0.01400	0.22400	6.350	98.000

## Universal Metal Part Numbers

Base P/N      Finish  
 XXXX      -      XXX

Finish Designation	Description	Advantages	SS Corrosion Rating
100	Heat Treated, Plain	Cost effective	N/A
103	Phosphate, 2 coats Paint	Cost effective, Moderate SS	96 Hours
139	2 Coats Gray Paint	Cost effective, Moderate SS	96 Hours
144	Zinc, Clear Chromate	Cost effective, Moderate SS	96 Hours
200	Phosphate, Plain	Cost effective, Limited SS	72 Hours
328	2 Coats Geomet	High SS resistance, hex-free	480 Hours
324	2 Coats Geomet & Black	High SS resistance, hex-free	480 Hours
930	Plain	Cost effective	N/A
941	Zinc, Bake, Clear Epigard	Cost effective, Limited SS	72 Hours
1430	Zinc, Bake, Clear Chromate	Cost effective, Limited SS	72 Hours
1440	Zinc, Bake, Clear Chromate	Cost effective, Moderate SS	96 Hours

REV7.1-07